



NOTES:
1) MATERIAL: 7075-T6 (OR T651/T6510/T6511/T62) ALUMINUM BAR
PER AMS-QQ-A-225/9 (OR AMS 4122/4123/4186/4187) OR
PER AMS-QQ-A-200/11
2) FINISH: HARD ANODIZE IAW MIL-A-8625 TYPE III, CLASS 2, COLOR BLACK;
PRETREAT PRC-DESOTO PR-148 ADHESION PROMOTER;
PRIME IAW MIL-P-23377J TYPE I CLASS N; 1-2 MIL MAX.
3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
4) UNITS: INCHES UNLESS OTHERWISE NOTED
5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
6) IDENTIFICATION: IDENTIFY WITH DART P/N "Default" USING FINE POINT PERMANENT INK MARKER
7) WEIGHT: lbs
8) PART DIMENSIONS CONTROLLED BY CAD MODEL FILE:

A	NEW RELEASE	DB	13.04.17
REV.	DESCRIPTION	BY	DATE
DESIGN	DB	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	DB		
CHECKED		DRAWING NO.	REV. PA1
MFG. APPR.		D4821	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		WINDSHIELD DEFLECTOR	NTS
DATE	13.04.17	COPYRIGHT © 2013 BY DART AEROSPACE LTD <small>THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.</small>	